



ROBUST FLOOR FINISH

TECHNICAL DATA SHEET

Packaging	Code
Quart	146-4830
Gallon	146-4846
5g Pail	146-4847

Description:

The ultimate in durability and exceptional gloss for little or low maintenance floor programs. High solid formulation designed to withstand the heaviest traffic, yet repair with a minimal low and high speed buffer program. It will maintain its exceptionally high gloss longer than conventional polishes by resisting scuffing, scratching, and dirt pick up. Low maintenance finish is designed to maintain a wet look shine that lasts longer between maintenance cycles. A perfect finish for maintenance programs that involve little buffing and/or burnishing.

Directions:

Ready to use.

Completely remove old finish and sealer from the floor.

Rinse well with a neutralizer.

When the floor is dry apply 3 uniform coats of finish allowing 30 minutes between coats.

Features & Benefits:

Extremely high initial gloss

Better detergent resistant

Improved scuff resistance in high traffic areas

Safety:

Personal Protection	B
Flammability	0
Health	1
Physical Hazard	0

0 =	Insignificant
1 =	Slightly
2 =	Moderate
3 =	High
4 =	Very high

Specifications:

Total Solids	30%
Colour	Milky White
Odour	Minimal
pH	8.4-8.8
Specific Gravity	1.04
Dry/Recoat Time	30 min dry to touch
Soil Resistant	Excellent
Stability	One year minimum
Freeze/Thaw	Passes 3 cycles but prevent from freezing
Long Term Removability	Excellent
Detergent Resistance	Excellent
Slip Resistance	yes- meets/exceeds ASTM D2047



Sudbury
345 Regent
Sudbury, Ont.
P3C 4E1
(705)675-5281
(705)675-8348(fx)

S.S. Marie
45 White Oak Drive, Unit 3
Sault Ste. Marie, Ont.
P6B 4J7
(705)949-9969
(705)949-3016(fx)

Timmins
167 Wilson Ave.
Timmins, Ont.
P4N 2R8
(705)268-3221
(705)268-3564(fx)